

# Matrox RT2000

## Installation procedure for the Matrox G450 as a secondary display.

This document provides information for installing the Matrox G450 for use as a second display with Matrox RT2000, using Windows 2000, Windows Me, or Windows 98 SE.

**Important** Before installing your secondary display card, make sure that you've correctly installed and configured your RT2000 hardware and software as explained in your *RT2000 Installation & User Guide*.

### To install your secondary display card

1. Power down your system, then install your G450 display card in a free PCI slot and connect your second computer monitor.
2. If you have a Windows 2000 system:
  - a. Turn on your computer and insert the Matrox RT2000 installation CD in your CD-ROM drive.
  - b. Windows detects your display card and the driver. Click **Yes** to install the driver.
  - c. Click **Finish**.
3. If you have a Windows Me or Windows 98 SE system, Windows detects your new display card and installs its driver from the Windows database.
4. When prompted, click **Yes** to restart your computer.
5. Right-click your Windows desktop background, then choose **Properties > Settings**.
6. In the provided display window, click the number "2" monitor, and then click **Yes** to enable the monitor.
7. Set your color palette (**Colors**) and display resolution (**Screen area**) to the same settings as your primary monitor. For more information on Windows monitor settings and changing your Windows Display Properties, see your Windows documentation.

### Notes

- On a Windows 2000 system, the proper installed driver version should be 5.35.011. On a Windows Me or Windows 98 SE system, the proper installed driver version should be 6.25.011. To verify your driver version, right-click your Windows desktop background, then choose **Properties > Settings > Advanced > Adapter > Properties > Driver**.
- Since the Matrox G450 is a DualHead display card, you can connect and configure a third monitor. However, video playback on your second or third monitor is not supported. When playing back clips in Adobe Premiere, leave the **Monitor** and **Clip** windows on your primary monitor (that is, the monitor connected to your Matrox Millennium Flex 3D Edition card).
- If you need to re-install the display driver for your Matrox G450, please use the drivers found on the RT2000 CD, in the `\Support\G400Flex3D\Win2000` or `\Support\G400Flex3D\Win98Me` directory.

---

© 2001 by Matrox Electronic Systems Ltd. All rights reserved.

**Disclaimer** Matrox Electronic Systems Ltd. reserves the right to make changes in specifications at any time and without notice. The information provided by this document is believed to be accurate and reliable. However, no responsibility is assumed by Matrox Electronic Systems Ltd. for its use; nor for any infringements of patents or other rights of third parties resulting from its use. No license is granted under any patents or patent rights of Matrox Electronic Systems Ltd.